

T +886 7 8216339 F +886 7 8216380
A 2F-1, 286-4, Xinya Rd., Qianzhen Dist., Kaohsiung City 806, Taiwan (R.O.C.)
M ushelt@hfaf.com.tw

AT-660

Durable C-6 Fluorinated Water & Oil Repellent Agent

AT-660 is a newly developed fluorochemical type water and oil repellent agent for various fibers. **AT-660** gives a perfect water and oil repellent effect to natural fibers such as cotton, synthetic fibers such as polyester, nylon and their blends, mixtures.

Textile finished with AT-660 keeps the excellent effect even after home-laundry or dry-cleaning.

General Composition Fluoroalkylacrylate copolymer

Properties Appearance Slightly yellow-brown emulsion

Ionicity Weakly cation

pH (100%) 2.0 ± 1.0 Solid contents Over 30

Features

&

Application

- AT-660 gives an excellent water and oil repellency to natural fibers such as cotton, synthetic fibers such as polyester, nylon and mixed fibers of natural.
- AT-660 is super durable type. Therefore it is highly durable even after home-laundry or dry cleaning.
- AT-660 also has an excellent compatibility with other chemicals, and enables to combine with resin, anti-static agent, fire-retardant agent and silicone based repelling agent.
- **AT-660** shows a good chemical stability due to low sensitivity to pH.
- AT-660 gives stable water and oil repellent effect from beginning to ending.



- T + 886 7 8216339 F + 886 7 8216380 A 2F-1, 286-4, Xinya Rd., Qianzhen Dist., Kaohsiung City 806, Taiwan (R.O.C.)

 M ushelt@hfaf.com.tw
- AT-660 is PFOA, PFOS, APEO, and Formaldehyde free product.
- AT-660 is not flammable. It is easily used and stored.

Direction for use

The optimal condition for AT-660 is different according to different target materials, and the need of the repelling power of water and oil. However, please treat the following method, Pad-Dry-Cure, depending on standard usage.

Cellulose fiber $: 2.00\% \text{ soln.} \sim 6.00\% \text{ soln.}$: 1.00% soln. $\sim 5.00\%$ soln. Synthetic fiber Blended fiber : 2.00% soln. $\sim 6.00\%$ soln.

Handling advice

Please avoid direct exposure to sunlight and keep in cool place.

Please prevent freezing in winter season.

It may make the target material darken in color to a certain extend. However, it will not affect the nature of the material and can be used safely.

Packing

1,000 kgs / IBC Tote

We strongly suggest that your company should perform operational test before using our formula.

